

**DON'T WAIT
...UNTIL IT'S TOO LATE !!!**

**PROTECT YOUR FAMILY!
PROTECT YOUR LIVESTOCK!
PROTECT YOUR INVESTMENTS!**

Fire Stomper

**THE IMPORTANCE OF REACTING QUICKLY
IS ESSENTIAL IN PROTECTING YOUR ASSETS!**

- Lower your insurance rates
- Affordable peace of mind
- Anyone can operate the Fire Stomper
- Easy to use



**The insurance savings alone may pay for the cost of the Fire Stomper
SAVE TIME, SAVE MONEY AND SAVE YOUR INVESTMENTS!**

Wild Fire... Front Line Attacker!

- ON & OFF ROAD FIRE APPARATUS
- PULL WITH YOUR UTILITY ATV OR TRUCK
- MANUFACTURE READY FOR AIR TRANSPORT
- LIGHT WEIGHT ALUMINUM, TIG WELDED TRAILER
- C.E.T SINGLE STAGE CENTRIFUGAL FIRE PUMP



POWERED BY:



TANK SUCTION



SUCTION INLET



MANIFOLD



CONTROL PANEL



STRAINER



Fire Stomper

A DIVISION OF BLUE OX EQUIPMENT

510 Morey Road, Sutton, VT 05867

(802) 467-3273

www.thefirestomper.com

info@thefirestomper.com

**The insurance savings alone
can pay for the cost of the
Fire Stomper!**

STANDARD OPERATING EQUIPMENT

- C.E.T single stage centrifugal fire pump, capable of pumping 225 GPM at 25 PSI
- 11 HP Honda - air cooled, 4 stroke, electric start, gas engine, 1/2 gallon of gas = 1 hour average run time
- Water/Foam storage - 150 gallon high density polypropylene water tank with an integrated 5 gallon foam cell
- Water Inlet - 2 1/2" inlet w/ cap & chain
- Suction Hose - Four 8' sections of 2 1/2" Kochek draft hose
- Suction Strainer - 2 1/2" floating Strainer w/ threaded coupling
- Outlet manifold valves, standard equipment:
 - 1 - garden hose outlet w/ ball valve shutoff
 - 1 - 1" NHT outlet w/ Akron ball valve shutoff
 - 1 - 1 1/2" NHT outlet w/ Akron ball valve shutoff (other configurations available as an upgrade)
- Foam System - Class A Scotty around the pump foam system standard up to 1.7% mixing capability
- Foam Nozzle - 30 GPM Scotty foam nozzle
- Hose - 100' of 1" forestry hose
- Storage rack - designed to hold 5- five gallon containers of foam.

OPTIONAL EQUIPMENT

- Spanner wrench holder w/ two wrenches
- Manual rewind hose reel w/ 150' of 1" rubber booster hose
- Aluminum hose tray with line pre-connect
- Extra forestry hose available



FIRE STOMPER TRAILER SPECIFICATIONS

FIRE STOMPER DIMENSIONS:

Trailer length 150" with tongue - Trailer width 5"

Trailer height - 55" to top of foam storage rack

FIRE STOMPER WEIGHT:

Fire Stomper empty weight: 1360 lbs.

Fire Stomper loaded weight: 2680 lbs. includes 150 gallons of water, 30 gallons of foam, 5 gallons of gas, self contained and ready to work for 10 hours

TRAILER MAIN FRAME:

1/8" x 2" x 4" - 6061 grade aluminum tubing, tig welded

TRAILER SIDES:

10 gauge polished aluminum tread plate, mechanically formed & tig welded

TONGUE:

Removable 1/4" x 3" x 3"

6061 grade aluminum tubing, tig welded & bolted

HITCH:

Standard 2" ball receiver

AXLES:

Two 2000 lbs. axles w/ hydraulic drum brakes

BRAKE MECHANISM:

Four wheel surge hydraulic

TIRES:

Four On & Off road, 20.5" x 10" x 8"

TOOL STORAGE:

Medium size lockable storage box, mounted on trailer tongue

WINCH:

Rear mounted 2300 lbs. pulling capacity with 50' cable.